


## Acis



|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| <b>Article number</b>                   | 4140601                                  |
| <b>EAN Code</b>                         | 8719979282073                            |
| <b>Statistical code</b>                 | 94051990                                 |
| <b>Warranty (year)</b>                  | 5                                        |
| <b>Application</b>                      | Terrace, Driveway, Path, Roof, Staircase |
| <b>Dimensions H x W x D</b>             | 20 mm x 40 mm x 40 mm                    |
| <b>Material</b>                         | RVS, Stainless steel 304                 |
| <b>Colour</b>                           | Silver gray                              |
| <b>IP class</b>                         | IP67                                     |
| <b>Protection class</b>                 | III                                      |
| <b>Drill diameter</b>                   | 30                                       |
| <b>Wattage (Total)</b>                  | 0.2                                      |
| <b>Net luminous flux (Lumen)</b>        | 5                                        |
| <b>Amount of lightsources per lamp</b>  | 1                                        |
| <b>Energy class</b>                     | N.A.                                     |
| <b>Light color</b>                      | Warm white                               |
| <b>Kelvin (Color temperature)</b>       | 3000                                     |
| <b>Lightsources includes</b>            | Yes                                      |
| <b>Replaceable lightsource</b>          | No                                       |
| <b>Light direction</b>                  | Upwards                                  |
| <b>CRI</b>                              | 75                                       |
| <b>Smart</b>                            | No                                       |
| <b>Cable length (meter)</b>             | 1.1                                      |
| <b>Cable size</b>                       | 20AWG                                    |
| <b>Minimum ambient temperature (°C)</b> | -20                                      |
| <b>Maximum ambient temperature (°C)</b> | 50                                       |
| <b>Number of luminaires in a pack</b>   | 1                                        |
| <b>Lifetime (hours)</b>                 | 25000                                    |
| <b>Start-up voltage (Volt)</b>          | 9                                        |
| <b>Dimmer</b>                           | No                                       |

|                                     |       |
|-------------------------------------|-------|
| <b>Suitable for external dimmer</b> | No    |
| <b>Overpassable</b>                 | Yes   |
| <b>AC/DC</b>                        | Yes   |
| <b>Adjustable</b>                   | No    |
| <b>Product weight (kg)</b>          | 0.071 |
| <b>Underwater</b>                   | No    |