

## Catalpa



|                                             |                                     |
|---------------------------------------------|-------------------------------------|
| <b>Article number</b>                       | 4121601                             |
| <b>EAN Code</b>                             | 5907800856422                       |
| <b>Statistical code</b>                     | 94051990                            |
| <b>Warranty (year)</b>                      | 5                                   |
| <b>Application</b>                          | Hedge, Bush, Border, Object / image |
| <b>Dimensions H x W x D</b>                 | 125 mm x 80 mm x 80 mm              |
| <b>Material</b>                             | RVS, Stainless steel 304            |
| <b>Colour</b>                               | Silver gray                         |
| <b>IP class</b>                             | IP44                                |
| <b>Protection class</b>                     | III                                 |
| <b>Drill diameter</b>                       | 0                                   |
| <b>Wattage (Total)</b>                      | 2.6                                 |
| <b>Net luminous flux (Lumen)</b>            | 195                                 |
| <b>Amount of lightsources per lamp</b>      | 1                                   |
| <b>Energy class</b>                         | F                                   |
| <b>Light color</b>                          | Warm white                          |
| <b>Kelvin (Color temperature)</b>           | 3000                                |
| <b>Article number lightsource (Techmar)</b> | 6323011                             |
| <b>Lightsource includes</b>                 | Yes                                 |
| <b>Replaceable lightsource</b>              | Yes                                 |
| <b>Lightsource replaceable by</b>           | MR16 LED GU5.3                      |
| <b>Light direction</b>                      | Forward                             |
| <b>Beam angle (degrees)</b>                 | 36                                  |
| <b>CRI</b>                                  | 83                                  |
| <b>Smart</b>                                | No                                  |
| <b>Cable length (meter)</b>                 | 1                                   |
| <b>Cable size</b>                           | 20AWG                               |
| <b>Minimum ambient temperature (°C)</b>     | -20                                 |
| <b>Maximum ambient temperature (°C)</b>     | 50                                  |
| <b>Number of luminaires in a pack</b>       | 1                                   |

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| <b>Lifetime (hours)</b>             | 25,000                                 |
| <b>Start-up voltage (Volt)</b>      | 9                                      |
| <b>Dimmer</b>                       | No                                     |
| <b>Suitable for external dimmer</b> | No                                     |
| <b>Overpassable</b>                 | Yes                                    |
| <b>AC/DC</b>                        | Yes                                    |
| <b>Fasteners</b>                    | Screws, Plugs, Ground spike, Allen key |
| <b>Adjustable</b>                   | No                                     |
| <b>Product weight (kg)</b>          | 0.37                                   |
| <b>Underwater</b>                   | No                                     |